

NMF-2PL-**xxx**A1C-BK

NIKOMAX
G. 652. D & G. 657. A1,

9/125

(A)-HF -40C, , 1


« »

FTTx


NMF-2PL-**xxx**A1 -BK
ITU-T G. 652.D & G. 657.A1.

1,2

(A)-HF.



SM 9/125



NIKOMAX NMF-2PL-004A1C-BK 4 x SINGLE MODE 9/125 ITU-T G. 652.D & G. 657.A1 Hr(A)-HF -40C DG23T 986M

NMF-2PL-xxxA1C-BK	
1	2
Single Mode 9/125	
ITU-T G.652.D & G.657.A1	
250 ± 10	
0,5	
1,2	
()-HF	
2 ± 0,1 5,1 ± 0,1	
14,0	
15	
30	
600	
220 H/	
-40 +60 °C. -40 +60 °C. 0 +60 °C.	
(),	
310 310 250	
1	

	1	2	3	4
NMF-2PL-001A1C-BK				
NMF-2PL-002A1C-BK				
NMF-2PL-004A1C-BK				

NMF-2PL-001A1C-BK	1	SM 9/125	(A)-HF	310 310 250	15,5
NMF-2PL-002A1C-BK	2	SM 9/125	(A)-HF	310 310 250	15,5
NMF-2PL-004A1C-BK	4	SM 9/125	(A)-HF	310 310 250	15,5